



## **UNIPHOS** HEADSPACE GAS ANALYZER $(O_2 \& CO_2)$



### **Uniphos** HEADSPACE GAS ANALYZER (O<sub>2</sub> & CO<sub>2</sub>)

The Headspace  $O_2 \& CO_2$  Analyzer is a battery- operated, portable analyzer used for the measurement of oxygen and  $CO_2$  in gas-flushed (CAP/MAP) food packages.

Modified Atmosphere Packaging (MAP) helps in preserving the food products in an atmosphere that has been modified to increase the shelf life of the packed products. The three main gases used in modified atmosphere packaging are  $O_{2^{\prime}}$  CO<sub>2</sub> and N<sub>2</sub>. The head space of any packaging contains any one of these gases or a mixture of these gases. The success of packaging depends on the packer's ability to correctly prepare the product and to control the concentrations of head space gas within the desired limits.

In case of N<sub>2</sub> flushed packaging, the Head Space Gas Analyzer helps to measure the quality of modified atmosphere by detecting raised levels of O<sub>2</sub>. The analyzer can also be used to determine the Oxygen & CO<sub>2</sub> concentration where the modified atmosphere is O<sub>2</sub> &CO<sub>2</sub> enriched (50-100%V/V).

The Headspace  $O_2 \& CO_2$  Analyzer uses a syringe needle sampling assembly to pierce the package and draw a sample into the analyzer for  $O_2 \& CO_2$  measurement. The oxygen sensor used in the analyzer is specifically designed for gas-flushed packaging measurements. It is an electrochemical, fast response sensor having excellent zero and span stability, and with an operating measurement range of 0-100%V/V Oxygen. The CO<sub>2</sub> Sensor is a NDIR type sensor with the range of 0-100%V/V.

# **UNIPHOS** HEADSPACE GAS ANALYZER (O<sub>2</sub> & Co<sub>2</sub>)

#### **SALIENT FEATURES:**

- Portable, battery operated
- Inbuilt data storage
- Inbuilt sampling pump
- Easy to operate and maintain
- Calibration with ambient air (O2 only) •
- USB charging



### **SPECIFICATION:**

Range	0 to 100% v/v (O2 & CO2)
Resolution	0.1% (O2) & 0.2% (CO2)
Accuracy of reading	± 1% (O2), ± 5% (CO2)
Sensor	O2 (Electrochemical), CO2 (NDIR)
Data Storage	4000 Records
Sampling Assembly	Needle Probe with Filter, PTFE tubing
Battery Capacity	3.75 V, 2800 mAh
Charger	USB mini B type; 5V, 1A
Size	192 mm X 106 X 43mm (Approx.)
Weight	500 gms



Due to continuous development, we reserve the right to change specifications without prior notice.

ISO 9001 BUREAU VERITAS Certification



Manufactured By: Uniphos Envirotronic Pvt. Ltd. P.O. Nahuli - 396 108 Tal. Umbergaon Dist: Valsad, Gujarat, India Tel.:+91-9909 994 042 7574 839 945

Safety & Environmental Monitoring Solutions

Marketing Office: Uniphos Envirotronic Pvt. Ltd. Readymoney Terrace, 4th Floor 167 Dr. Annie Besant Road Worli, Mumbai - 400 018, India Tel.:+91(22) 6123 3500 Fax:+91(22) 2497 8119



IND17.5449/U/Q

Email: gasdetection@uniphos-envirotronic.com Web: www.uniphos-she.com