



PRODUCT SPECIFICATION DATA SHEET

UNIPHOS PRO

METHANE GAS MONITOR



| GAS RELATED SPECIFICATIONS | | |
|----------------------------|--|--|
| Gas Detected | Methane | |
| Concentration Range | 0-100% LEL | |
| Resolution | 1% LEL | |
| Detection Principle | Pellistor Sensor | |
| Accuracy | Inherently +/- 3-5% (but also depends on the accuracy of the calibration gas & method) | |
| Sampling | Internal Sample Draw Diaphragm Pump 400-800 ml/min | |

| DISPLAY & INDICATOR SPECIFICATIONS | |
|------------------------------------|--|
| Display | Backlit 20x4 Alphanumeric OLED Display LEDs indicate status of power & sampling |
| Function Keys | For Increment, Decrement and Setting |
| Electronic Alarm | 85db Audio Alarm, Visual LEDs |

| ELECTRONICS AND ELECTRICAL SPECIFICATIONS | | |
|---|---|--|
| Electronics | Micro Controller based instrument | |
| Connectivity | Mini USB for PC connectivity | |
| Data Logging | Data logging facility for up to 3000 samples Data logging with user settable features Records gas readings along with time/date | |
| Power Source | 7.4 V Li-Ion rechargeable battery pack | |

| PHYSICAL SPECIFICATIONS | | |
|------------------------------------|---|--|
| Operating Temperature Range | 0 to 40 Degree Celsius | |
| Operating Pressure | Ambient +/- 10% | |
| Enclosure | Hi Impact ABS Plastic Enclosure | |
| Weight | 500 grams (1.10 lb.) | |
| Dimensions | H x W x D: 205 x 108 x 38 mm | |
| Standard Accessories | Battery Charger, Data downloading cable and dust filter | |