



PRODUCT SPECIFICATIONS DATA SHEET

UNIPHOS-500WS MULTICHANNEL SCANNER



Key Features

- > Microprocessor based system with inbuilt memory.
- LED display (6 digit 7-segment) for display of gas concentration sequentially of all 8 channels. Three digits will show the channel number Viz. 1 to 8 & remaining three digits will show gas concentration (max. 000 to 999).
- > 3 LEDs and relays for Low, High & Fault alarm conditions
- Inbuilt SMPS
- Front panel is provided with four keys viz. SET, UP, DOWN and ENTER

| ELECTRONICS & ELECTRICAL SPECIFICATIONS | |
|---|---|
| Display | 3-digit 7 segment LED display per channel |
| No. of Channels | 8 |
| Input signal | Industrial Standard 4-20 mA analog signal |
| Alarms | 3 Potential free relays for LOW, HIGH & FLT alarm |
| Function Keys | UP, DOWN, SET & ENTER Keys |
| Input Power | 110-230 V AC +/- 10 %, 50/60 Hz |
| Output Power | 24VDC (for transmitters only) |

| PHYSICAL SPECIFICATIONS | |
|-------------------------|--|
| Temperature | 0 to 50 °C |
| Pressure | Ambient +/- 10% |
| Enclosure | FRP/FLP |
| Weight | FRP: 6 kg approx. FLP: 17 kg approx. |
| Dimensions | FRP: L=300mm, W=175mm, D=350mm FLP: L=245mm, W=200mm, D=425mm |