

Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

Methyl Bromide CH_3Br

TWA (TLV): 1 ppm

STEL (TLV): NA

SMB-4M

Flammable Range: 10-16%

Specification:

Measurement Range	Extended	Standard	Extended
	10 – 20 ppm	20 – 300 ppm	300 – 600 ppm
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1.5 minutes per pump stroke (100 mL)		
Color Change	White → Yellow		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F).		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle (Double Tube)	$\text{CH}_3\text{Br} + \text{Cr}^{6+} + \text{H}_2\text{SO}_4 \rightarrow \text{Br}_2$ Br + o - Tolidine → Yellow reaction product		
Relative standard deviation	± 10 – 15 %		

* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Halogens		+	Yellow
Tetrachloroethylene		+	Yellow
Trichloroethylene		+	Yellow
1,2-Dichloroethane	200	No	No Effect
1,1,1-Trichloroethane	50	No	No Effect

Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



Manufactured By: Uniphos Envirotronic Pvt. Ltd.
Nahuli (PO), Umbergaon (Tal.)
Valsad (Dist), Gujarat, India – 396108

Rev.0823